

Baifu Air Electrostatic spray gun

LE30

Suitable application

Metal: all surfaces and shapes of metal objects Plastic: TV frame, bumper, motorcycle plastic parts, Phone boxes, side door mirrors, cell phones, computers

Wood: doors, door frames, windows, desks, chairs, headboards

Glass: Perfume bottles and any other bottles

Advantages

Medium pressure atomization, 1 kg/cm2, good atomization, high oating efficiency!

The paint valve and circulation valve are external, easy to maintain, low in cost, and highly dependable!

It can be metered when spraying. Back flow when not spraying. Easy to control film thickness, high solid content and metallic paint, fully flow and stir for use!

Fully insulated electrostatic spray gun design, less paint wrapping, save paint, overcome the disadvantages of high conductivity and water-based paint electric leakage, and meet the requirements of various paints!

With built-in high voltage and external high voltage design, users can choose the best solution according to their needs!

Long-life tungsten steel needle tip, suitable for switching once per second!

Specification


Model	LE30-A	LE30-B		
HV Type	External HV	Built-in HV		
HV Controller	BPS100/BPS290	IPS930E		
Gun Size(LxDia.)	318 x Ø80mm	318 x Ø80mm		
Gun Weight	1550g	1870g		
Flat Nozzle	Standard	Standard		
Round Nozzle	Metal/Plastic steel Optional			
Paint Valve	External	External		
Cir. Valve	External	External		
Max. Air consumptionm	600NL/min.	600NL/min.		
Resistance	50 Meg-Ohm	150 Meg-Ohm		
Atomizing Pressure	0.5~1.5 Kg/cm ²	0.5~1.5 Kg/cm ²		
Weight(w/ bracket)	2540 g	2860 g		

CLPPS 3D Light curtain perspective coating system

ight curtain 3D automatic letection, spraying only when there re object in front of the gun, saving aint and reducing environmental ollution and cleaning costs at and thin objects to be coated, he spray gun will automatically eep an equidistant distance from he object to avoid collision lamage of the spray gun and poor

'recise switch on/off gun, control he fat edge of static electricity void paint sagging, uniform film hickness, and good surface inishing.

dopt constant-speed full-stroke eciprocating to avoid uneven listribution of paint on the upper nd lower ends of variable-stroke receiver eciprocating machine.





VRF constant speed reciprocator

Electrostatic spray gu

Light curtain recognition computer control

Syn. pulse generato



Baifu Technology Corp. Long Wall Trading Co.,Ltd

9F, No.83, Zhong Cheng Road New Taipei City 236 Taiwan Fax:886-2-2268-4086 Tel: 886-2-2268-4088 BFcoating www.bfcoating.com

Taichung:886-4-2358-8755 Tainan: 886-6-270-9257 🎗 Beijing:86-10-6488-2666 Shanghai:86-21-6483-9459 Tianjin:86-22-5885-3955 Kunshan:86-512-5745-8588 Dongguan:86-769-8541-5416 Xiamen:86-592-6074-228

Gear pump



Baifu Air Electrostatic spray gun LE30



Reciprocator specification							
	Vertical		Horizontal				
Model	VR	VRF	HR				
Stroke	Variable	Fix	Variable				
Track design	Linear guideway						
Payload(Kg)	40	40	15				
Max. Stroke(M)	STD 1.5/2.0, Optional 2.5/3.						
Speed(M/min.)	15-45	15-60	0-30				
Back/forth motion	STD :						
back/forth motion	Option: Electric						
C/V tracking800mm	Inverte						
Safety level		·					
Rated motor voltage	STD 380V, 3 phase 50/60 Hz*						
*0							

*Opt.:other voltage, explosion proof servo motor















	Solvent base paint			Water base paint(insulation)				
Combination No.	10#	20#	30#	10i#	20i#	30i#	40i#	
Gear pump unit	General	One for multi	Servo motor type	Insulation	One for multi	Servo motor type	sealing type	
Specification	Explosion proof			None-Explosion proof				
Gear pump	Alloy steel/stainless steel DLC/tungsten steel			Stainless steel DLC/tungsten steel				
Motor	AC inverter		AC Servo	AC inverter		AC Servo	AC inverter	
Installation	Vertical wall mount	Floor mount	Vertical wall mount	Vertical wall mount	Floor mount	Vertical wall mount	Floor mount	

Paint pump VS. Paint supply station















Double diaphragm pump

N1.068 Fiber nylon S1.068 Stainless steel A1.068 Aluminum A1.288 Full set PS4 Pedal water tray PSiA Insulation PSiB Insulation

Application cases:























